



CSBLED-HVG

Swingblade Exit, Surface Mount, LP, Zoneworks Hive, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CSBLED-HVG
MIC	AUA00000037101
Description	Swingblade Exit, Surface Mount, LP, Zoneworks Hive, All Pictograms, Single or Double Sided
Construction	Metal frame, White End Caps with Acrylic & Polycarbonate Diffuser
Mounting	Wall or Ceiling mount on a slide connect bracket – Single & Double Sided NOTE: If product is suspended below the Ceiling or Mounted on a metal surface the Swingblade bracket cover plate accessory (P/N: 2740105) is required to cover the mains terminal
Dimensions L x W x H	See diagram below
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage charger
Diffuser	All directional inserts included in the box
Lamp(s)	24 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar – 100,000hour
Operating Voltage	240V AC: 50Hz
Supply Current	0.057A
Power Factor	0.398
Power Consumption	3.8W (Standby), 5.6W (Max)
Inrush Current (Peak/Duration)	30A/500µs
Earth Leakage	0.315mA
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	C ₀ =D6.3 C ₉₀ =E3.2
Viewing Distance	24M
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550070	Battery
8002185	240V LED Panel
8003211	Emergency Driver
8003450	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

