



CUBPRO-D2

CLEVERTRONICS LP ULTRABLADE PRO, DALI-2



PRODUCT INFORMATION

Part Number	CUBPRO-D2
MIC	AUA02211030001
Description	Ultrablade Pro Exit, Recessed Mount, LP Lithium Iron Phosphate, Picto All, Double Sided, DALI-2
Construction	PC/ABS body with PC diffuser
Mounting	Recessed mount, double sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Earth Leakage	0.331
Inrush Current	13.08
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
AS2293 Classification	C0=E6.3 C90=E6.3
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002178	LED Strip
AUM02270530001 CUBPRO-CKIT-D2	Driver Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.