



## CUBPRO-HV-V-BLK

Ultrablade Pro Exit, Recessed Wall Mount, Vertical, LP,  
Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	CUBPRO-HV-V-BLK
MIC	AUA02810270002
Description	<a href="#">go</a> Ultrablade Pro Exit, Recessed Wall Mount, Vertical, LP, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS Body with PC Diffuser
Mounting	Recessed Wall Mount, Single or Double Sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Vertical legend, all directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
Inrush Current (Peak/Duration)	13.08A / 84µs
Earth Leakage	0.341mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.25 C90=B1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Markings (RCM)	



## CUBPRO-HV-V-BLK

Ultrablade Pro Exit, Recessed Wall Mount, Vertical, LP,  
Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002178	Lamp Assembly
AUM02870020002 CUBPRO-CKIT-HV	Emergency Driver
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order