



CUBPRO-HVG

CLP Premium Ultrablade Pro, Recessed Mount, Zoneworks Hive



PRODUCT INFORMATION

Catalogue Number	CUBPRO-HVG
MIC	UKA02810060002
Description	CLP Premium Ultrablade Pro, Recessed Mount, Zoneworks Hive
Construction	PC/ABS Body with PC Diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp (s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	0.38
Supply Current	0.044A
Power Consumption	1.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Peak/Duration)	13.08A/84µs
Earth Leakage	0.331mA
IP Rating	IP20
Viewing Distance	30m
Operating Temperature	0°C to 40°C
Luminaire Classification	X 1 AFG 180
Compliance Marking	
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553050	Battery
8002178	LED Panel
UKM02870090002	Emergency Driver
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.