



CUBPRO-HVG-V

Ultrablade Pro Exit, Recessed Wall Mount, Vertical, LP, Zoneworks HIVE,
All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CUBPRO-HVG-V
MIC	AUA02910160001
Description	Ultrablade Pro Exit, Recessed Wall Mount, Vertical, LP, Zoneworks HIVE, All Pictograms, Single or Double Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Recessed Wall Mount, Single or Double Sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Vertical legend, all directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	TBA
Supply Current	TBA
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
Inrush Current (Peak/Duration)	TBA
Earth Leakage	TBA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1 C90=B1
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Markings (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550150	Battery
8002178	LED Panel
AUM02970030001	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order