



CUBPRO-SM-D2

CLEVERTRONICS LP ULTRABLADE PRO, SURFACE MOUNT, DALI-2



PRODUCT INFORMATION

Part Number	CUBPRO-SM-D2
MIC	AUA02211060001
Description	LP Premium Ultrablade Pro surface mount blade Exit, DALI-2
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
Inrush Current (Max)	
Earth Leakage	
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002178	LED Strip
8003130	Driver
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.