



CUBPRO-SM-D2

Ultrablade Pro Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CUBPRO-SM-D2				
MIC	UKA0000008101				
Description	Ultrablade Pro Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)				
Weight	1.1kg				
Operating Mode	Maintained				
Testing System	DALI-2				
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	12 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Factor	0.38				
Supply Current	0.05A				
Power Consumption	1.8W (Standby), 3.9W (Max)				
Inrush Current (Peak/Duration)	18.9A / 138µs				
Earth Leakage	N/A				
Viewing Distance	30m				
IP Rating	IP20				
Rated Emergency Duration	180 minutes				
Operating temperature	0°C to 40°C				
Compliance Marking					
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8003850	Emergency Driver
8002178	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.