



CUBPRO-SM-HVG-BLK

Ultrablade Pro Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	CUBPRO-SM-HVG-BLK
MIC	AUA02910070001
Description	Ultrablade Pro Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT.
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8003135	PCA:CUBPRO-SM Driver CT10142-L9 DALI Reg,CTP,HV,ZW
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order