CLEVERTRONICS CLP ULTRABLADE PRO SURFACE MOUNT (ZONEWORKS HIVE)



PRODUCT INFORMATION		
Catalogue Number	CUBPRO-SM-HVG	
MIC	UKA02810040001	
Description	CLP Premium Ultrablade Pro Surface Mount Blade Exit	
Construction	PC/ABS body with PC Diffuser	
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided	
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)	
Weight	1.0kg	
Operating Mode	Maintained	
Testing System	Zoneworks XT HIVE (RF)	
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics	
Charging Method	Intelligent Current Limited Constant Voltage	
Diffuser	All directional inserts included in the box	
Lamp(s)	12 x LED, 100,000 hours	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	1.8 Watts (Standby), 3.9 Watts (Max)	

Version: October 2020-1

clevertronics.co.uk



PRODUCT INFORMATION		
Viewing Distance	30m	
Rated Emergency Duration	180 minutes	
IP Rating	IP20	
Operating temperature	0°C to 40°C	
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) 	
Luminaire Classification	X 1 AGF 180	
Conformity	BS EN 60598.2.22, BS 5266	

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.	
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)	
8003137	PCA: CUBPRO-SM UK Driver, CT10142-L9, OWC	
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna	

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

Version: October 2020-1

clevertronics.co.uk

