



CUBPRO-SM-TH-D2-R

Ultrablade Pro Exit, Surface Mount, LP, DALI-2 Emergency, Theatre Version, Running Man, Single Sided



PRODUCT INFORMATION	
Part Number	CUBPRO-SM-TH-D2-R
MIC	AUA00000001201
Description	Ultrablade Pro Exit, Surface Mount, LP, DALI-2 Emergency, Theatre Version, Running Man, Single Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Single-Sided, Wall & Ceiling Mount
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man
Lamp(s)	12 x LED, 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.0434A
Power Factor	0.38
Power Consumption	1.7W (Standby), 4W (Max)
Inrush Current (Peak/Duration)	14.669A / 66µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002178	LED Panel
8003503	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.