

## **CUBPRO-SM-TH-HVG-R**

CLEVERTRONICS LP ULTRABLADE PRO EXIT, SURFACE MOUNT, ZONEWORKS XT HIVE



PRODUCT INFORMATION	
Part Number	CUBPRO-SM-TH-HVG-R
MIC	AUA02960030001
Description	Ultrablade Pro Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4W/4.1W (STANDBY/MAX)
Inrush Current (Max)	
Earth Leakage	
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002178	LED Strip
8003503	Emergency Driver (**Pack)
8003560	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

