

CLEVERTRONICS CLP ULTRABLADE PRO SURFACE MOUNT



PRODUCT INFORMATION

Catalogue Number	CUBPRO-SM
MIC	UKA02310020001
Description	CLP Premium Ultrablade Pro Surface Mount Blade Exit with Clevertest Plus Enabled
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.8 Watts (Standby), 3.9 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8003137	PCA: CUBPRO-SM UK Driver, CT10142-L9, OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.