




CUBPRO-TH-D2-RL

Ultrablade Pro Exit, Recessed Ceiling Mount, LP, DALI-2, Theatre Version, Running Man Arrow Left, Single Sided



PRODUCT INFORMATION

Part Number	CUBPRO-TH-D2-RL
MIC	AUA02260570001
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, LP, DALI-2, Theatre Version, Running Man Arrow Left, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running Man Arrow Left, Double Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
Inrush Current (Max)	12.4A, 264µs
Earth Leakage	0.324mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550150	Battery
8002178	LED Strip
AUM02270530001 CUBPRO-CKIT-D2	Emergency Driver Pack
8003062	Emergency Node – DALI-2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.