

Ultrablade Pro Exit, Recessed Ceiling Mount, LP, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided



PRODUCT INFORMATION

Catalogue Number	CUBPRO-TH-HVG-R
MIC	AUA02960050001
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, LP, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp (s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT.
CUBPRO-CKIT-HVG	Ultrablade Pro, Control Only, LP, HVG (incl Hive node)
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order