

CUBPROCLEVERTRONICS LP ULTRABLADE PRO EXIT



PRODUCT INFORMATION	
Part Number	CUBPRO
MIC	AUA02310090002
Description	LP Premium Ultrablade Pro Blade Exit, Enabled with Clevertest Plus
Construction	PC/ABS Body with PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 8.mm x 157mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	<u>&</u>

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550150	Battery
8002178	LED Strip
AUM02370020002 CUBPRO-CKIT	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

