

## CLEVERTRONICS CLP ULTRABLADE PRO



### PRODUCT INFORMATION

Catalogue Number	CUBPRO
MIC	UKA02310030001
Description	CLP Premium Ultrablade Pro Blade Exit with Clevertest Plus Enabled
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.8 Watts (Standby), 3.9 Watts (Max)

## PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• LED driver – Over temperature protection, Overload protection, Short-circuit protection, No-load protection</li> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> </ul>			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598-2-22, BS 5266			

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
UKM02370060001	CUBPRO-CKIT-60 OWC, Ultrablade Pro,Control Only, UK CTP, LP, 60mA OWC

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.