



CWELED-A-D2

IP66/67 Weatherproof Exit, Surface Mount, LP, DALI-2
Emergency, All Pictograms, Single or Double Sided, Acrylic Cover



PRODUCT INFORMATION

Part Number	CWELED-A-D2
MIC	AUA00000000901
Description	IP66/67 Weatherproof Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Acrylic Cover
Construction	Acrylic clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Battery Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	TBC
Power Factor	TBC
Power Consumption	2.8W/4W (STANDBY/MAX)
Inrush Current (Peak/Duration)	15A/260µs
Earth Leakage	0.333mA
IP Rating	IP66/67
IK Rating	IK04
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D4, C90=E3.2, C180=E2.5, C270=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8002329	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order