






## CWELED-A-HVG

IP66/67 Weatherproof Exit, Surface Mount, LP, Zoneworks XT  
Hive, All Pictograms, Single or Double Sided, Acrylic Cover



PRODUCT INFORMATION	
Catalogue Number	CWELED-A-HVG
MIC	AUA02920090001
Description	IP66/67 Weatherproof Exit, Surface Mount, LP, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Acrylic Cover
Construction	Acrylic clear cover, glass reinforced nylon PA66 base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	220-240V~ 50Hz
Power Consumption	2.8W (Standby), 4W (Max)
Inrush Current (Peak/Duration)	15A / 260μS
Earth Leakage	0.333mA
IP Rating	IP66/IP67
IK Rating	IK04
Operating Temperature	0°C to 40°C
Projected Light Source Life (LSL)	100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
AS2293 Classification	C0=D4, C90=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II Double Insulated  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC purposes only)



## CWELED-A-HVG

IP66/67 Weatherproof Exit, Surface Mount, LP, Zoneworks XT  
Hive, All Pictograms, Single or Double Sided, Acrylic Cover

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002329	Emergency Driver
8002710	LED Panel
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order