



## CWELED-D2-BLK

LP Premium Weatherproof Emergency Exit, DALI-2 Emergency, Black



PRODUCT INFORMATION	
Part Number	CWELED-D2-BLK
MIC	AUA00000028101
Description	LP Premium Weatherproof Emergency Exit, DALI-2 Emergency, Black
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.043A
Power Factor	0.394
Power Consumption	3.2 Watts (Standby), 4.3 Watts (Max)
Inrush Current (Peak/Duration)	12.517/82μs
Earth Leakage	N/A
IP Rating	IP66/IP67
Impact Rating	IK10
Viewing Distance	24m
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D4, C90=E2.5
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002329	Emergency Driver
8002710	Emergency LED Strip
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order