






## CWELED-D2

IP66/67 Weatherproof Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided



PRODUCT INFORMATION	
Part Number	CWELED-D2
MIC	AUA02211080001
Description	IP66/67 Weatherproof Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided
Construction	Polycarbonate clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	220-240V~ 50Hz
Power Consumption	2.5W (Standby), 3.7W (Max)
Inrush Current (Peak/Duration)	12.517A / 82μs
Earth Leakage	0.333mA
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
Projected Light Source Life (LSL)	LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
AS2293 Classification	C <sub>0</sub> =D4 C <sub>90</sub> =E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Appliance Class	 Class II Double Insulated  Noiseless (Clean) Earth (Ground) Terminal (Not a Protective Earth and used for EMC purposes only)
Compliance Marking (RCM)	



## CWELED-D2

IP66/67 Weatherproof Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms,  
Single or Double Sided

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8002329	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order