




CWELED-HVG-BLK

CLEVERTRONICS LP CLEVERFIT EXIT



PRODUCT INFORMATION

Part Number	CWELED-HVG-BLK
MIC	AUA02920070001
Description	LP Premium Cleverfit Emergency Exit
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
IP Rating	IP66/67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D4 C90=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	Battery
8002329	Driver
8002710	LED Strip
8003560	RF Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order