



CWELED-HVG-WM

Weatherproof Exit, Wall Mount, LP, Zoneworks XT Hive 2.4GHz,
All Pictograms, Single Sided



PRODUCT INFORMATION

Part Number	CWELED-HVG-WM
MIC	AUA02920020001
Description	Weatherproof Exit, Wall Mount, LP, Zoneworks XT Hive 2.4GHz, All Pictograms, Single Sided
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=55Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.8 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.6
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	BATT:LP 3.2V 1500mAh 390mm lead, noBRKT.
8002120	LED: PCA:DLED Cleverfit LightStrip,CT10152-D2
CWELED-CKIT-HVG	EM DRIVER: WP LED Exit, Control Kit, LP, HVG (incl Hive node)
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order