



CWELED-HVG

Weatherproof Exit, Surface Mount, LP,
Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	CWELED-HVG
MIC	AUA02920010001
Description	Weatherproof Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided
Construction	Polycarbonate clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D4 C ₉₀ =E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT.
8002710	LED: PCA:Duris LED Strip Cleverfit Pro CT10276-D3
8002329	EM Driver: PCA: CT10164-L6 6C43 DALI, Dali Reg, HV
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.