





CWFLED-HVG

CLEVERTRONICS CLP LED WEATHERPROOF SUPALITE (ZONWORKS HIVE)



PRODUCT INFORMATION	
Part Number	CWFLED-HVG
MIC	UKE02820010001
Description	CLP LP Premium LED weatherproof supalite flood unit, surface mounted Emergency Light
Construction	Polycarbonate
Mounting	Surface wall mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm.
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 320lm per lamp head
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)
Total lumen output	640lm (Emergency)

PRODUCT INFORMATION					
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	X	0	ADF	180	
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking	 				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
UKM02870110001	CCPLED-WP-18V350C-CKIT-HVG, LED Power Pack, 18V 350mA, IP Loom, LP, OWC
1100550	WP Led Head, c/w Led's & Loom, Gland
8003290	PCA: UK RF Node CT10720-A1 Ext Antenna Horizontal

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.