

CLEVERTRONICS CLP LED WEATHERPROOF SUPALITE



PRODUCT INFORMATION

Catalogue Number	CWFLED
MIC	UKE02320010001
Description	CLP LP Premium LED weatherproof supalite flood unit, surface mounted Emergency Light, , Enabled with Clevertest Plus
Construction	Polycarbonate
Mounting	Surface wall mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm.
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 320lm per lamp head
Operating Voltage	240V AC; 50Hz
Total lumen output	640lm (Emergency)
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP65			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	0	AD	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
UKM02370160001	CCPLED-WP-18V350C-CKIT, LED Power Pack, 18V 350mA, IP Loom, LP, OWC
1100550	WP Led Head, c/w Led's & Loom, Gland

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.