

CLEVERTRONICS LP WEATHERPROOF SURFACE MOUNT WITH TWIN LIFELIGHT PRO PODS



PRODUCT INFORMATION

Part Number	CWP2LIFE-PRO-WPPOD
Description	LP Premium LifeLight PRO, high performance, surface mounted IP65 Emergency with twin rotatable LED Pods, Enabled with Clevertest Plus
Construction	Polycarbonate
Mounting	Surface mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.5 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D160 C ₉₀ =D160

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP

