

# CIRCLITE PREMIUM



## Premium LED Circular Emergency light








The Premium Circlite is an IP54 rated luminaire that is ideal for applications such as corridors, stairwells and walkways.

Constructed with a polycarbonate body and opal diffuser and with a large terminal block the Premium Circlite is also easy to install.

With an emergency classification of D25, LED technology and available with microwave sensor technology the Premium Circlite is a leader in this space.

### Applications

- |   |   |
|---|---|
|  Office Buildings |  Car Parks         |
|  Public Amenities |  Railway Stations  |
|  Schools          |  Sports Facilities |

### Features and Benefits

- AS/NZS 2293.3 compliant
- D25 emergency classification
- IP54
- LED lamps
- Lithium Iron Phosphate
- Microwave sensor options
- Large terminal block



# CIRCLITE PREMIUM

ORDERING INFORMATION		LP		240V	
TEST OPTIONS / PART #	Standard	CCIRC	CCIRC-MS-HL	FCIRC	FCIRC-MS-HL
	DALI Driver	CCIRC-DD	-	FCIRC-DD	-
	Clevertest Plus System Compatible	Yes		-	
	DALI	CCIRC-DALI	CCIRC-MS-HL-DALI	-	-
	Zoneworks® XT Hive	CCIRC-HV	CCIRC-MS-HL-HV	-	-
Carton Quantity		5			
Weight - Single (Carton)		1.8kg			
Dimensions (Diameter x H)		327mm x 100mm			

POWER, LAMPS AND BATTERY		LP		240V	
Power Consumption (Standby / Max)		1W / 16W	7W / 18W	12W	14W
Lamp(s) (CCT / Life)		LED 4,000K Natural White, 50,000hrs, Ra>80 (L70 / B50)			
Nominal Lumen Output		1300lm		1300lm	
Battery		Lithium Iron Phosphate		-	
Voltage / Capacity (mAh)		3.2V / 3000mAh		-	
Charging Method		Intelligent Current Limited Constant Voltage		-	


TECHNICAL SPECIFICATIONS	LP		240V	
	Operating Mode	Sustained	Non-Emergency	
	Construction - Body / Diffuser	Polycarbonate / Polycarbonate		
	Voltage (V) (Frequency (Hz))	220-240V (50Hz)		
	Operating Temperature	1°C to 40°C		
	Ingress Protection Rating (IP)	IP54		

CLASSIFICATION	LP
C0	D25
C90	D25

SPACING TABLE AND MOUNTING HEIGHTS - AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)															
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m	9.0m	10.0m	
D25	11.5	13.2	14.8	15.7	16.1	16.4	16.8	17.3	17.6	18.1	18.3	18.2	17.8	17.2	

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

\*Warranty information located at: <https://clevertronics.com.au/warranty-statement/>



**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products.  
All features and specifications are subject to change without prior notice.  
\_PRODUCT SHEETS - ANZ Circlite Premium 04OCT22

