

RCM DECLARATION OF CONFORMITY

Document No: Date:	CLEV-RCM-WEATHERPROOFEXIT24M 28 October 2021	
We:	Clevertronics Pty Ltd 1 Caribbean Drive Scoresby VIC 3179 Australia T: +61 3 9559 2700 E: <u>Productenquiry@clevertronics.com.au</u> ABN: 64 136 264 349	Clevertronics Pty Ltd Unit 22/761 Great South Road Penrose, Auckland 1061, New Zealand T: +64 800 548 448 E: <u>Productenquiry@clevertronics.com.au</u> NZBN: 9429042377382

declare that the CWELED-HV and the following associated product codes

aWELED-bb-cc-dd-ee-ff

aWELED-A-bb-cc-dd-ee-ff

aWELED-TH-bb-cc-dd-ee

aWELED-bb-WM-cc-dd-gg-ff

aWELED-bb-WM-IPREM-cc-dd-ff

aWELED-bb- FZR-gg-ff aWELED-bb- FZR-IPREM-gg-ff

Where,

a = L	L10 Battery
a = C	LP Battery
bb = Blank	Manual Test/Clevertest Plus (CTP)
bb = ZW	Zoneworks XT
bb = HV	Zoneworks XT HIVE
bb = DATA	Zoneworks DATA
bb = DALI	DALI Registered
cc = Blank	Standard fitting (Default)
cc = 4HR	4-hour emergency run-time fitting
dd = Blank	Non-Tamperproof version (Default)
dd = TP	Tamperproof version
ee = Blank	Changeover Supply from self-contained battery – Default
ee = UPS	Changeover Central Supply from a UPS (240VAC)
ff = Blank	Housing Colour (Default)
ff = BLK	Housing Colour – Black
ff = "Custom colour code"	Custom defined colour code
gg = Blank	One-box Solution
gg = E	EXIT Decal
gg = R	Running Man Decal
gg = RL	Running Man Left Arrow Decal
gg = RR	Running Man Right Arrow Decal
gg = DS-E	Double sided EXIT Decal
gg = DS-R	Double sided Running Man Decal
gg = VR	Vertical Running Man Decal
Cleve	Responsible Supplier Number E7500 rtronics is registered with ERAC EESS and ACMA



RCM DECLARATION OF CONFORMITY

are in conformity with the requirements of the:

- AS/NZS 4417.1:2012 & AS/NZS 4417.2:2018 in-scope electrical equipment and AS/NZS 3820:2009 (Essential safety requirements for electrical equipment)
- Radiocommunications Labelling (Electromagnetic Compatibility) Notice 2017 made under section 182 of the Radiocommunications Act 1992
- > Australian Communications and Media Authority (ACMA) for Electromagnetic Compatibility (EMC).

The above products meet requirements of the following standards:

AS/NZS 2293.3:2018Emergency lighting and exit signs for buildings - Emergency luminaires and
exit signsAS 60598.2.22:2019Luminaires - Part 2.22: Particular requirements - Luminaires for emergency
Lighting (IEC 60598-2-22:2017 (ED.4.1) MOD)AS CISPR 15:2017Limits and methods of measurement of radio disturbance characteristics of
electrical lighting and similar equipment (CISPR 15:2013+AMD1:2015
(ED.8.1) MOD)

(IN)

Michael Duce National Systems and Engineering Manager

