

CLEVERFIT PRO EXIT LIGHT



Modern and Slimline Architectural Exit

The Cleverfit Pro Exit offers a practical lithium powered egress solution in a slimline, architecturally pleasing design. The Cleverfit Pro has a simple slide connect steel bracket and can be either wall or ceiling mounted.



Applications

-  Office Buildings
-  Retail outlets
-  Showrooms
-  Apartments
-  Shopping Centres



Features and Benefits

- Tested to BS EN 60598-2-22
- Compliant to EN1838 and ISO7010
- Low 3.7W standby power consumption
- Wall and ceiling mount with easy slide connect
- All directional decals in one box
- Lithium Iron Phosphate or Nanophosphate® battery
- DALI® and Zoneworks® test options available
- Clevertest Plus System compatible



CLEVERFIT PRO EXIT LIGHT

ORDERING INFORMATION		CLP	L10
TEST OPTIONS PART NO	Standard	CCFPRO	LCFPRO
	Clevertest Plus System Compatible	Yes	Yes
	DALI	CCFPRO-DALI	LCFPRO-DALI
	Zoneworks® XT Hive	CCFPRO-HVG	LCFPRO-HVG
	Theatre Version	CCFPRO-TH	LCFPRO-TH
Carton Quantity	5		
Weight - single (carton)	2.5kg (13.0kg)		
Dimensions (L x W x H)	367mm x 72mm x 214mm		
Directional Options	All Directional Inserts Included (Excluding theatre versions)		
Directional Options (Theatre Only)	Add Suffix to Part No, Double Sided -DS , Left Arrow -RL, Right -RR, Up -RU, Down -RD. eg CCFPRO-TH-DS-RL		

* for additional variants please refer to the Clevertronics Product Guide or website.

POWER, LAMPS AND BATTERY	CLP	L10
Power Consumption (Standby / Max)	3.7W / 4.8W	3.8W / 5.0W
Lamp(s)	100,000 Hour LED	
Battery	Lithium Iron Phosphate	Lithium Nanophosphate®
Voltage (V) / Capacity (mAh)	3.2V / 3200mAh	3.3V / 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage	

TECHNICAL SPECIFICATIONS	CLP	L10
Operating Mode	Maintained	
Voltage (V) Frequency (Hz)	220-240V(50Hz)	
Construction - Body / Diffuser	PC-ABS / PC	
Viewing Distance	30m	
Mounting Type	Wall & Ceiling (Single & Double Sided)	
Operating Temperature	0°C to 40°C	
Ingress Protection Rating (IP)	IP20	

ACCESSORIES	CLP	L10
Cantilever Bracket	CLVRBRT-CFPRO	CLVRBRT-CFPRO
Wireguard (Wall Mount)	2530050	2530050
Wireguard (Ceiling Mount)	2530110	2530110

LUMINAIRE CLASSIFICATION	CLP				L10			
Without Automatic Testing	X	1	AG	180	X	1	AG	180
With Automatic Testing	X	1	AFG	180	X	1	AFG	180

PROTECTION
Battery overvoltage & overcurrent protection
Battery deep discharge protection
Supply voltage polarity reversal protection
Battery short-circuit protection (charging will resume upon removal of fault)



Dimensions (mm)

*Warranty information located at: <https://clevertronics.co.uk/product-warranty-statement/>

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

clevertronics.co.uk

362 Stockley Close, West Drayton, London UB7 9BL

Clevertronics International UK Ltd trading as Clevertronics, with registered number 11249539, whose registered office is at 843 Finchley Road London NW11 8NA. 248UK UK Catalogue 2021

