

JUMBO LED EXIT LIGHT



Jumbo Exit for Larger Viewing Distances

The Jumbo LED Exit caters for 50m viewing distance applications by using a 250mm high pictograph.

Featuring a robust steel housing with slide-in diffusers and backplates for single and double-sided configurations, the Jumbo LED Exit is easy to install as a wall or ceiling mounted exit.



Applications

- | | |
|---|--|
|  Warehouses |  Stadiums |
|  Factories |  Halls |
|  Car Parks |  Train Stations |

Features and Benefits

- Tested to BS EN 60598-2-22
- Compliant to EN1838 and ISO7010
- Wall and ceiling mount
- All directional decals in one box
- Lithium Iron Phosphate or Nanophosphate® battery
- DALI® and Zoneworks® test options available
- Clevertest Plus System compatible



CLP LITHIUM IRON PHOSPHATE
PREMIUM
PROVEN PROJECT PERFORMANCE

L10 LITHIUM NANOPHOSPHATE®
OPTIMUM
NOTHING ELSE COMPETES WITH NANOPHOSPHATE®



JUMBO LED EXIT LIGHT

ORDERING INFORMATION		CLP				L10			
PART NO	Standard	CJELED-50				LJELED-50			
	Clevertest Plus System compatible	Yes				Yes			
	DALI	CJELED-50-DALI				LJELED-50-DALI			
	Zoneworks® XT Hive	CJELED-50-HVG				LJELED-50-HVG			
Carton Quantity		1							
Weight		7.3kg							
Dimensions (L x W x H)		630mm x 100mm x 320mm							
Directional Options		All directional inserts included in the box							

POWER, LAMPS AND BATTERY		CLP				L10			
Power Consumption (Standby / Max)		3.2W / 5.6W							
Lamp(s)		100,000 Hour LED							
Battery type		Lithium Iron Phosphate				Lithium Nanophosphate®			
Voltage (V) / Capacity (mAh)		3.2V / 6400mAh				3.3V / 5000mAh			
Charging Method		Intelligent Current Limited Constant Voltage							

TECHNICAL SPECIFICATIONS		CLP				L10			
Operating Mode		Maintained							
Voltage (V) (Frequency (Hz))		220-240V (50Hz)							
Construction - Body / Diffuser		Powder Coated Metal / Acrylic							
Viewing Distance		50m							
Mounting Type		Wall and Ceiling Single and Double Sided							
Operating Temperature		0°C to 40°C							
Ingress Protection Rating (IP)		IP20							

LUMINAIRE CLASSIFICATION		CLP				L10			
Without Automatic Testing	X	1	AG	180	X	1	AG	180	
With Automatic Testing	X	1	AFG	180	X	1	AFG	180	

PROTECTION
Battery overvoltage & overcurrent protection
Battery deep discharge protection
Supply voltage polarity reversal protection
Battery short-circuit protection (charging will resume upon removal of fault)



Dimensions (mm)

*Warranty information located at: <https://clevertronics.co.uk/product-warranty-statement/>

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

clevertronics.co.uk

362 Stockley Close, West Drayton, London UB7 9BL
 Clevertronics International UK Ltd trading as Clevertronics, with registered number 11249539, whose registered office is at 843 Finchley Road London NW11 8NA. 248UK UK Catalogue 2021

