

ARGONAUT ENTRY



exterior canopy applications, and boasts a low-profile, die-cast powder-coated housing and a UV-stabilized, impact-resistant polycarbonate lens. With selectable colors and outputs, it delivers more than 16,800 lumens of powerful illumination.

Applications



Car Parks



Factories



Sports Facilities





Railway Stations



Public Amenities

Features and Benefits





- Switchable colour (3000K/4000K/5000K)
- Switchable Outputs (80W/100W/120W)
- IP65 Ingress Protection
- **IK08 Impact Protection**











ARGONAUT ENTRY


| ORDERING INFORMATION | | STANDARD |
|------------------------|--------------------------|-----------------|
| TEST OPTIONS / PART # | Standard | ARGOENTRY |
| | Motion Sensors | · |
| | Carton Quantity | 1 |
| | Weight - Single (Carton) | 3.6KG |
| Dimensions (W X H X D) | | 346 x 346 x 105 |

| TECHNICAL SPECIFICATIONS | STANDARD | |
|--------------------------------|---|--|
| Construction - Base | Die-Cast Aluminium | |
| Construction - Diffuser | UV-Stabilised Polycarbonate | |
| Voltage (V) Frequency (Hz) | 220-240V~ 50Hz | |
| Nominal Lumen Output | 16,883Im (146.9Im/W) @ default (see table next page) | |
| Power Consumption | 114.9W @ default (refer to Power Consumption table below for more details) | |
| Lamp | LED Panel Module | |
| Lamp(s) (CCT/Life) | Switchable 3000K/4000K (default) /5000K L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 135,000hr L80/B50 Ta 40°C; LM80 Report >54,000hr, Projected 80,000hr L90/B50 Ta 40°C; Projected 40,000hr | |
| Operating Temperature | 0°c to 40°c | |
| Ingress Protection Rating (IP) | IP65 | |
| Imapct Rating (IK) | IK08 | |

 $^{^{*}\,\}mbox{On/off}$ function can be managed by astronomical clock when used with Hive Combine

| POWER CONSUMPTION | MAIN LAMP ON | LUMEN OUTPUT | LUMENS / WATT | |
|-------------------|--------------|--------------|---------------|--|
| OUTPUT 1 (80W) | STD | STD | STD | |
| 3000K | 85.5W | 11563lm | 135.2 lm/W | |
| 4000K | 82.7W | 12601lm | 152.3 lm/W | |
| 5700K | 84.2W | 12682lm | 150.6 lm/W | |
| OUTPUT 2 (100W) | | | | |
| 3000K | 104.7W | 13730lm | 131.1 lm/W | |
| 4000K | 100.7W | 15192lm | 150.9 lm/W | |
| 5700K | 102.9W | 15104lm | 146.8 lm/W | |
| OUTPUT 3 (120W) | | | | |
| 3000K | 120.0W | 15198lm | 126.7 lm/W | |
| 4000K DEFAULT | 114.9W | 16883lm | 146.9 lm/W | |
| 5700K | 117.8W | 16824lm | 142.8 lm/W | |

^{*}Warranty information located at: https://clevertronics.com.au/warranty-statement/



clevertronics.co.nz clevertronics.com.au

Dimensions (mm)

1 Caribbean Drive, Scoresby VIC 3179 P +61 3 9559 2700 F +61 3 9559 2799 E info@clevertronics.com.au

