




## DYGC-CP-DS-RAOW-HVG

CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT  
Hive, Running Man Arrow One Way, Double Sided



Dynamic LEDs Sequencing Arrow

### PRODUCT INFORMATION

Part Number	DYGC-CP-DS-RAOW-HVG
MIC	AUA02950140002
Description	CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) activated on VF/24V Input Trigger and capable of being activated in power-on and battery-backed mode with added functionality of Dynamic Green activation over the XT Hive network.
Testing System	Zoneworks XT HIVE (RF) 2.4
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, 1 Element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	3.1 Watts (Standby), 7.5 Watts (Max)
Power Factor	0.415
Inrush Current (Peak/Duration)	17.4A / 132μS
Earth Leakage	0.350mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.25 C90=C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	EM Driver
8003025	LED Strip
8003560	NODE - Hive

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order