



## DYGC-CP-DS-RAOW-HVG

### CLEVEREVAC DYNAMIC GREEN EXIT SIGN – DOUBLE SIDED (ZONWORKS XT HIVE)



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION					
Part Number	DYGC-CP-DS-RAOW-HVG				
MIC	UKA02850100001				
Description	CLP Premium CleverEVAC Dynamic Green EXIT Sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green Enhancement				
Construction	PC/ABS body with PC diffuser				
Mounting	Ceiling Mount, Double-sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.0kg				
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Double Sided Pictograph, Two Elements (Running Man with Arrow)				
Lamp(s)	LED panel, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.1W (Standby), 7.5W (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>				
Luminaire Classification	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">X</td> <td style="padding: 2px 10px;">1</td> <td style="padding: 2px 10px;">AFG</td> <td style="padding: 2px 10px;">180</td> </tr> </table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack
8003330	Node - Hive

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice