



DYGC-CP-R-HVG

CleverEVAC Dynamic Green Exit, Surface Mount, LP,
Zoneworks HIVE, Running Man, Single Sided



Dynamic LEDs Sequencing Inwards

PRODUCT INFORMATION

Part Number	DYGC-CP-R-HVG
MIC	AUA02950130002
Description	CleverEVAC Dynamic Green Exit, Surface Mount, LP, Zoneworks HIVE, Running Man, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall Mounted Single Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – sequencing inward green LEDs activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode, with the added functionality of Dynamic Green activation over the HIVE network. Dynamic Green default set to activate upon mains power fail.
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, 1 Element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
Power Factor	0.415
Inrush Current (Peak/Duration)	17.4A / 132μs
Earth Leakage	0.328mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.25 C ₉₀ =C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3, Codemark CM20237 (AUS), CM20236 (NZ)
Compliance Marking (RCM)	



DYGC-CP-R-HVG

CleverEVAC Dynamic Green Exit, Surface Mount, LP,
Zoneworks HIVE, Running Man, Single Sided

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8003025	Emergency LED Strip
8002927	Emergency Driver
8003560	Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.