



DYGC-CP-R-HV

CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT
Hive, Running Man, Single Sided



Dynamic LEDs Sequencing Inwards

PRODUCT INFORMATION

Part Number	DYGC-CP-R-HV
MIC	AUA02850140002
Description	CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT Hive, Running Man, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger. Capable of being activated in power-on and battery-backed mode, with additional functionality of Dynamic Green activation over the XTHive network.
Testing System	Zoneworks XT HIVE
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, 1 Element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
Power Factor	0.415
Inrush Current (Max)	17.4A, 132uS
Earth Leakage	0.328mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.25 C ₉₀ =C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack
8003191	Node - Hive

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order