



DYGC-CP-RD-HVG

CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Down, Single Sided



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION

Part Number	DYGC-CP-RD-HVG		
MIC	UKA02850130001		
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Down, Single Sided		
Construction	PC/ABS body with PC diffuser		
Mounting	Ceiling Mount, Double-sided		
Dimensions L x W x H	367mm x 72mm x 214mm		
Weight	2.0kg		
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode		
Testing System	Zoneworks XT HIVE (RF)		
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics		
Charging Method	Intelligent Current Limited Constant Voltage		
Diffuser	Pictograph, Two Elements (Running Man, Arrow Down)		
Lamp(s)	LED panel, 100,000 hours		
Operating Voltage	220-240V AC; 50Hz		
Power Consumption	3.1W (Standby), 7.5W (Max)		
Viewing Distance	30m		
Rated Emergency Duration	180 minutes		
IP Rating	IP20		
Operating temperature	0°C to 40°C		
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 		
Luminaire Classification	X	1	AFG 180
Conformity	BS EN 60598-2-22, BS 5266		

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack
8003330	Node - Hive

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice