



DYGC-CP-RD

CleverEvac Dynamic Green Exit, Surface Mount,
CLP, Running Man Arrow Down, Single Sided



PRODUCT INFORMATION

Part Number	DYGC-CP-RD
MIC	UKA00000000201
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Running Man Arrow Down, Single Sided
Material	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained Sequencing arrows (green LEDs) activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	N/A – Manual Test Switch
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
240V Driver	N/A
Charging Method	Intelligent current limited constant voltage
Power Consumption	2.8W (Standby), 7.2W (Max)
Power Factor	0.415
Inrush Current (Max)	17.4A @ 132μ
Earth Leakage	0.358 mA
IP Rating	IP20
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Marking	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Emergency Driver
8003025 x 2	Emergency Lamp

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order