




## DYGC-CP-RL-HVG

CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Running Man Arrow Left, Single Sided



Dynamic LEDs Sequencing Arrow

### PRODUCT INFORMATION

Part Number	DYGC-CP-RL-HVG
MIC	AUA02950060001
Description	CleverEvac Dynamic Green Exit, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Running Man Arrow Left, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing arrows activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, 2 Elements (Running Man and Arrow Left)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.25 C <sub>90</sub> =C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002927	PCA: DYxx Driver Board #CT10142-L9
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.