



## DYGC-CP-RL-HVG

CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Left, Single Sided



Dynamic LEDs Sequencing Arrow

### PRODUCT INFORMATION

Part Number	DYGC-CP-RL-HVG			
MIC	UKA02850150001			
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Left, Single Sided			
Construction	PC/ABS body with PC diffuser			
Mounting	Ceiling Mount, Double-sided			
Dimensions L x W x H	367mm x 72mm x 214mm			
Weight	2.0kg			
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	Two Elements (Running Man with Arrow)			
Lamp(s)	LED panel, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	3.1W (Standby), 7.5W (Max)			
Inrush Current (Max)	17.4@132µS			
Earth Leakage	0.352mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack
8003330	Node - Hive