



DYGC-CP-RR

CleverEvac Dynamic Green Exit, Surface Mount, CLP, Running Man Arrow Right, Single Sided



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION					
Part Number	DYGC-CP-RR				
MIC	UKA00000000301				
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Running Man Arrow Right, Single Sided				
Construction	PC/ABS body with PC diffuser				
Mounting	Ceiling / Wall mounted single sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.0kg				
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode				
Testing System	N/A				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Two Elements (Running Man with Arrow)				
Lamp(s)	LED panel, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	2.8W (Standby), 7.2W (Max)				
Inrush Current (Max)	17.4@132μS				
Earth Leakage	0.352mA				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 				
Luminaire Classification	<table border="1"> <tr> <td>X</td> <td>1</td> <td>AG</td> <td>180</td> </tr> </table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice