



## DYGC-CP-RU-HVG

CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Up, Single Sided



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION					
Part Number	DYGC-CP-RU-HVG				
MIC	UKA02850120001				
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Up, Single Sided				
Construction	PC/ABS body with PC diffuser				
Mounting	Ceiling Mount, Double-sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.0kg				
Operating Mode	Maintained – Sequencing Arrows (Green LEDs) Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	Pictograph, Two Elements (Running Man, Arrow Up)				
Lamp(s)	LED panel, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.1W (Standby), 7.5W (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack
8003330	Node - Hive

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice