



## DYGC-CP-SND-NC-R-HVG

CLEVEREVAC DYNAMIC GREEN EXIT SIGN WITH SOUND ESCAPE,  
ZONWORKS XT HIVE 2.4GHz



Dynamic LEDs Sequencing Inwards &  
Sounder Activated

### PRODUCT INFORMATION

Part Number	DYGC-CP-SND-NC-R-HVG
MIC	AUA02950020001
Description	LP Premium CleverEVAC Dynamic Green EXIT Sign, with Volt Free (VF) & 24V Interface for ON/OFF activation of Dynamic Green Enhancement and directional / locatable Sounder (Sound Escape), Zoneworks XT Hive 2.4GHz
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	446mm x 214mm x 72mm
Weight	2.4kg
Operating Mode	Maintained – Sequencing inward green LEDs & Sounder activated on VF/24V input and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh Nickel Cadmium, 3.6V 600mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.0 Watts (Standby), 10 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.25 C90=C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
1510310	BATT:3xAA NiCad Battery Pk. 600mAh SBS. (Sounder)
8002927	DRIVER: PCA: DYxx Driver Board #CT10142-L9
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.