




DYGC-UP-DS-RAOW-HVG

CleverEvac Dynamic Green Exit, Recessed Mount, LP, Zoneworks XT
Hive, Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION

Part Number	DYGC-UP-DS-RAOW-HVG
MIC	AUA00000021102
Description	CleverEvac Dynamic Green Exit, Recessed Mount, LP, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with Acrylic diffuser
Mounting	Recessed Ceiling, Double-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Operating Mode	Maintained – with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green Enhancement, sequencing arrows (green LEDs) and capable of being activated in power-on and battery-backed mode. Dynamic GREEN default set to activate upon mains power fail.
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Double sided Pictograph, two elements (Running Man with Arrow)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	0.366
Supply Current	0.054A
Power Consumption	3.1 Watts (Standby), 7.5 Watts (Max)
Inrush Current (Peak/Duration)	15.9A / 140µs
Earth Leakage	0.328mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E5; C90=C32
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
AUM02970540001	Emergency Driver
8003560	Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.