



DYGC-UP-WM-R-HVG

CleverEvac Dynamic Green Exit, Wall Mount, LP, Running Man, Single Sided, Zoneworks Hive (RF)



PRODUCT INFORMATION

Part Number	DYGC-UP-WM-R-HVG
MIC	AUA00000017701
Description	CleverEvac Dynamic Green Exit, Wall Mount, LP, Running Man, Single Sided, Zoneworks Hive (RF)
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing Inward Green LEDs Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Zoneworks Hive (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.1W (Standby), 5.0W (Max)
Inrush Current (Max)	15.9A/140µs
Earth Leakage	0.326mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E4, C90=C32
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8003325-MOD	LED Assembly
AUM02970540001 DYGC-UP-CKIT-HVG	EM Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order