




DYGL-CP-R-HVG

CleverEvac Dynamic Green Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man, Single Sided



Dynamic LEDs Sequencing Inwards

PRODUCT INFORMATION

Part Number	DYGL-CP-R-HVG
MIC	AUA01950140001
Description	CleverEvac Dynamic Green Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing inward green LED activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. Dynamic GREEN default set to activate upon mains power fail
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
Inrush current (Max)	17.4A@132uS
Earth Leakage	0.360mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2.5, C ₉₀ =E1.6, C ₂₇₀ =E1.6, C ₁₈₀ =B2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002927	Driver
8003191	HIVE Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.