



DYGL-CP-RR-HV

CLEVEREVAC DYNAMIC GREEN EXIT SIGN



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION	
Part Number	DYGL-CP-RR-HV
MIC	AUA01850260001
Description	L10 Optimum CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) or 24V interface for ON/OFF activation of Dynamic Green Enhancement. Capable of ON/OFF activation of Dynamic Green Enhancement over the XT HIVE Network. Dynamic GREEN default set to activate upon mains power fail.
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing arrows activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. Dynamic GREEN default set to activate upon mains power fail
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Two elements (Running Man and Arrow Right)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
Inrush Current(Max)	TBD
Earth Leakage	0.327mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =C1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002927	EM Driver
8003191	RF Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.