DYGL-CP-SND-NO-R-HVG

CleverEvac Dynamic Green Exit, Surface Mount, L10 Nanophosphate, Normally Open, Sounder, Zoneworks XT Hive, Running Man, Single Sided

Dynamic LEDs Sequencing Inwards & Sounder Activated

PRODUCT INFORMATION

Part Number	DYGL-CP-SND-NO-R-HVG
MIC	AUA01950030001
Description	L10 Lithium Nanophosphate CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green Enhancement and directional/locatable sounder (Sound Escape)
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	446mm x 214mm x 72mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing inward green LEDs & Sounder activated on VF/24V input and capable of being activated in power-on and battery-backed mode. Normally Open (NO) version – dynamic green and sound activated (turned on) when contact interface is closed.
Testing System	Zoneworks XT HIVE (RF) 2.4gHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh Nickel Cadmium, 3.6V 600mAh – for sounder unit
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.0 Watts (Standby), 10 Watts (Max)
Inrush Current (Max)	17.4A @132µS
Earth Leakage	0.299mA
IP Rating	IP20
Operating Temperature	1˚C to 40˚C
AS2293 Classification	C0=E2.5, C90=E1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
8002925	Driver
8003025	LED Strip
8003560	Hive Node
1510311	Sounder Module

www.cleverevac.com.au