



DYGL-CP-SND-NO-R

L10 Lithium Nanophosphate CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green Enhancement and directional/locatable sounder (Sound Escape)



Dynamic LEDs Sequencing Inwards & Sounder Activated

PRODUCT INFORMATION

Part Number	DYGL-CP-SND-NO-R
MIC	AUA01550060001
Description	L10 Lithium Nanophosphate CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green Enhancement and directional/locatable sounder (Sound Escape)
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	446mm x 214mm x 72mm
Weight	2.4kg
Operating Mode	Maintained – Sequencing inward green LEDs & Sounder activated on VF/24V input and capable of being activated in power-on and battery-backed mode. Normally Open (NO) version – dynamic green and sound activated (turned on) when contact interface is closed.
Testing System	Manual Testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh Nickel Cadmium, 3.6V 600mAh – for sounder unit
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.0 Watts (Standby), 10 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.6, C90=E1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
1510310	3xAA NiCad Battery Pk. 600mAh SBS.
8002927	PCA: DYxx Driver Board #CT10142-L9

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order