



## DYGL-UP-DS-RAOW-HVG

CleverEvac Dynamic Green Blade Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided



### PRODUCT INFORMATION

Part Number	DYGL-UP-DS-RAOW-HVG
MIC	AUA01950150001
Description	CleverEvac Dynamic Green Blade Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with Acrylic diffuser
Mounting	Recessed, Double-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Operating Mode	Maintained – Sequencing arrows (green LEDs) activated on VF/24V input Trigger and capable of being activated in power-on and battery-backed mode. <b>From 1<sup>st</sup> of April 2022 Dynamic GREEN default set to activate upon mains power fail</b>
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Double sided Pictograph, two elements (Running Man with Arrow)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.1 Watts (Standby), 5.0 Watts (Max)
Inrush Current (Max)	15.9A@140uS
Earth Leakage	0.326mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5; C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
AUM01970320001 DYGL-UP-CKIT-HVG	Driver Pack
8003191	Hive Node

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.