



DYRC-CP-R-HVG

CLEVEREVAC DYNAMIC GREEN & RED X EXIT SIGN



Dynamic LEDs Sequencing Inwards



Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION

Part Number	DYRC-CP-R-HVG
MIC	AUA02950010001
Description	LP Premium CleverEVAC Dynamic Green and Red X EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 214mm x 80mm
Cut-Out	N/A
Weight	2.0kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.5 Watts (Standby), 9.0 Watts (Max)
Inrush Current (Max)	17.4A, 132μS
Earth Leakage	N/A
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =E1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8002920	Driver
8003560	HVG Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.